





PROPORCIONÁLNÍ DÁVKOVAČE

Typ	Přípoj.	By Pass	Max. průtok (m ³ /h)	Max. tlak (bar)	Ztráta odporem (bar)	Celk. náplň (m ³)	Teplota vody		Tepl. prostředí		Rozměry		Balení	
							(°C)	(°F)	(°C)	(°F)	H (cm)	L (cm)		
	Dosaphos 200	1/2" - 1/2"	ne	2	10	0,2	1215	5-40	41-104	5-50	41-122	15	6	kelímek
	Dosaphos 250	1/2" - 1/2"	ano	2	10	0,2	1215	5-40	41-104	5-50	41-122	15	6	kelímek
	Dosaphos Dima	1/2" - 1/2"	ano	1,5	10	0,2	1215	5-40	41-104	5-50	41-122	19,5	4	kelímek
	Dosaphos Dima	1/2" - 3/4"	ano	1,5	10	0,2	1215	5-40	41-104	5-50	41-122	19,5	4	kelímek
	Souprana odvápnovače 200	1/2" - 1/2"	ne	2	10	0,2	(12÷15)x8	5-40	41-104	5-50	41-122	15	6	kufřík
	Souprana odvápnovače 250	1/2" - 1/2"	ano	2	10	0,2	(12÷15)x8	5-40	41-104	5-50	41-122	15	6	kufřík
	Souprana odvápnovače Dima	1/2" - 1/2"	ano	1,5	10	0,2	(12÷15)x8	5-40	41-104	5-50	41-122	19,5	4	kufřík
	Souprana odvápnovače Dima	1/2" - 3/4"	ano	1,5	10	0,2	(12÷15)x8	5-40	41-104	5-50	41-122	19,5	4	kufřík
	Dosaphos 500	1" - 1"	ne	5,8	10	0,2	100	5-40	41-104	5-50	41-122	18	11	krabice
	Dosaphos 600	1" - 1"	ne	5,8	10	0,2	120	5-40	41-104	5-50	41-122	23	11	krabice
	Dosaphos 700	1" - 1"	ne	5,8	10	0,2	120	5-40	41-104	5-50	41-122	23	13	krabice